Thermoid®

PRODUCT SPECIFICATIONS

SANI-WHITE[™] – WHITE BELTING





Description:	72"x2P APT70 WHT NBR 3/64xFS (S10) (1,2) SANI-WHITE
	24092821722
Product Construction	Smooth X Friction (White Nitrile on Treated Polyester Fabric)
Color	White
Compound Formulation	Nitrile
Fabric	Treated Polyester
Nominal Overall Gauge	0.096 ± 0.020 in (2.4 ± 0.5 mm)
Nominal Weight	0.60 ±10% lbs./ft ² (2.93 ±10% kg/m ²)
Rated Working Tension	70 lbs./inch (12 N/mm)
Top Cover Surface	Smooth
Bottom Cover Surface	Friction
Minimum Pulley Diameter	2 in (51 mm)
Temperature Range	20° to +212°F (-6° to +100°C)
Special Standards	USDA/FDA Approved
Cover Coefficient of Friction	1.0 nominal Steel (1.0 nominal Cardboard)
Bottom Coefficient of Friction	0.30 to 0.35 Steel (0.35 to 0.40 Cardboard)
Available Width(s)	72"
Typical Applications	 Meats, poultry and bakery Hot, oily foods Fruit and vegetable processing
Benefits	 Matte finish to help reduce eye strain on inspection lines Exceptional resistance to oil, grease, fats, food acids and moisture Smooth cover resists abrasion and makes for easier cleaning Polyester fabric is low stretch and moisture resistant

Phone: 800-543-8070

Email: info@thermoid.com

www.thermoid.com

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.