

SANI-WHITE™ – WHITE BELTING



representative image

Description:	72"x2P PNT100 WHT NBR 3/64xFS (S10) (1,2) SANI-WHITE
Product Number	<ul style="list-style-type: none"> • 24282821722 Belt Length 540' and Above • 24282821723 Belt Length 539' and Below
Product Construction	Smooth X Friction (White Nitrile on Treated Polyester/Nylon Fabric)
Color	White
Compound Formulation	Nitrile
Fabric	Treated Polyester/Nylon
Nominal Overall Gauge	0.109 ± 0.020 in (2.8 ± 0.5 mm)
Nominal Weight	0.76 ±10% lbs./ft ² (3.71 ±10% kg/m ²)
Rated Working Tension	100 lbs./inch (18 N/mm)
Top Cover Surface	Smooth
Bottom Cover Surface	Friction
Minimum Pulley Diameter	3 in (76 mm)
Temperature Range	20° to +212°F (-7° to +100°C)
Special Standards	USDA/FDA Approved
Cover Coefficient of Friction	1.0 nominal Steel (1.0 nominal Cardboard)
Bottom Coefficient of Friction	0.30 max Steel (0.32 max Cardboard)
Available Width(s)	72'
Typical Applications	<ul style="list-style-type: none"> • Meats, poultry and bakery • Hot, oily foods • Fruit and vegetable processing
Benefits	<ul style="list-style-type: none"> • Exceptional resistance to oil, grease, fats, food acids and moisture • Smooth cover resists abrasion and makes for easier cleaning • Low stretch and good fastener retention

Phone: 800-543-8070

Email: info@thermoid.com

www.thermoid.com

HBD/Thermoid is not responsible for possible errors in catalogues, brochures, websites and other materials, and may change such information without notice. HBD Thermoid reserves the right to modify its products without notice, including products already on order, as long as the modified product meets any agreed-upon specifications. All trademarks in this material are the property of the HBD Industries Inc., or its subsidiaries.